



FEATURES

1. Gold-plated plugs
2. compliant ROHS,1440P.
3. With UL/CUL3 standard

ELECTRICAL SPECIFICATION:

1. Withstanding voltage: 300VDC 0.1SEC
2. Insulation Resistance: 5Mohm 300VDC

LENGTH(mm)	1000±100
------------	----------

Type A PIN	Signal Assignment	Type A PIN
1 Blue	[Circuit diagram showing twisted pair]	Blue 1
2 ground		ground 2
3 white		white 3
4 Blue	[Circuit diagram showing twisted pair]	Blue 4
5 ground		ground 5
6 white		white 6
7 Blue	[Circuit diagram showing twisted pair]	Blue 7
8 ground		ground 8
9 white		white 9
10 Blue	[Circuit diagram showing twisted pair]	Blue 10
11 ground		ground 11
12 white		white 12
14 Blue	[Circuit diagram showing twisted pair]	Blue 14
17 ground		ground 17
19 white		white 19
15 Yellow	[Circuit diagram showing twisted pair]	Yellow 15
16 Oregor		Oregor 16
13 white	[Circuit diagram showing twisted pair]	white 13
18 red		red 18
SHELL		SHELL

DESCRIPTION&SPECIFICATIONS

6. Both Side print logo, White word. logo:
5. 28AWG OD=3.0*14.5mm
4. High Speed HDMI Cable with Ethernet 1440P E329703 (UL) TYPE C13 SHIELDED ---AWM 20276 80° C 30W VW-1 ROHS.
3. MOLDING TYPE: PVC black 45-60P
2. White aluminum casing
1. HDMI TYPE A PLUG, 19PIN(Pins Gold-Plated, SHELL Gold-Plated)

APPROVED	CHECKED	DRAWING	DESIGNED
DESCRIPTION	MODEL NO.	SCALE	FIT
DRAWING NO.	ELE6001M		
FINISHING			
MATERIAL		SYM	DATE
			2010/06/10
			REVISION
			A1
			3RD ANGLE
			UNITS:MM