ADV4008
8-Speaker Distribution Hub

This multi-speaker distribution hub can be mounted on a wall, in a cabinet, or in a standard 19-inch rack system. It includes 8 stereo speaker outputs. Spring-loaded, push-button terminals are color-coded and will accept 12-22ga wire. The hub features integrated impedance protection that can be enabled or disabled, depending on the type of volume control that is used.

IMPORTANT: Check your amplifier for impedance specifications prior to operating or disabling the impedance protection circuit.

With the impedance protection switched ON, the hub will handle up to 60W RMS per Channel. With the impedance protection switched OFF, the hub will handle up to 100W RMS per Channel.

Dimensions: 19in W x 3-1/5in H x 2-1/4in D

Impedance Protection "ON" (60W RMS/CH)								
Ohms	Ohms/speaker							
to Amplifier	Pair 1	Pair 2	Pair 3	Pair 4	Pair 5	Pair 6	Pair 7	Pair 8
7.0	4							
5.0	4	4						
4.33	4	4	4					
4.0	4	4	4	4				
3.8	4	4	4	4	4			
3.66	4	4	4	4	4	4		
3.57	4	4	4	4	4	4	4	
3.5	4	4	4	4	4	4	4	4
11.0	8							
7.0	8	8						
5.66	8	8	8					
5.0	8	8	8	8				
4.6	8	8	8	8	8			
4.33	8	8	8	8	8	8		
4.14	8	8	8	8	8	8	8	
4.0	8	8	8	8	8	8	8	8

Impedance Protection "OFF" (100W RMS/CH)								
Ohms	Ohms/speaker							
to Amplifier	Pair 1	Pair 2	Pair 3	Pair 4	Pair 5	Pair 6	Pair 7	Pair 8
4.0	4							
2.0	4	4						
1.33	4	4	4					
1.0	4	4	4	4				
0.8	4	4	4	4	4			
0.66	4	4	4	4	4	4		
0.57	4	4	4	4	4	4	4	
0.5	4	4	4	4	4	4	4	4
8.0	8							
4.0	8	8						
2.66	8	8	8					
2.0	8	8	8	8				
1.6	8	8	8	8	8			
1.33	8	8	8	8	8	8		
1.14	8	8	8	8	8	8	8	
1.0	8	8	8	8	8	8	8	8